

# W SERIES

F000330  
W17As

F000319  
W17P

F000446  
W440A

F000313  
W440P

W17As



W440A



W17As / W17P

W440A / W440P



## THE ONE WAY TO HAVE ALL THE FIVE W'S ANSWERED

L'unica cassa acustica ad avere una scocca unica ultra resistente anche per coloro che vogliono ascoltare buona musica durante l'apocalisse.

Compatta, versatile, leggera e di facile installazione, la serie è corredata di grande potenza e impatto sonoro, vincente su ogni punto di discussione, apprezzata e richiesta in numeri esorbitanti in tutto il mondo grazie alla sua famosa resistenza alle intemperie.

Questa linea di casse acustiche è stata progettata, infatti, per resistere e durare nel tempo, senza perdere nel campo dell'affidabilità e della qualità sonora; un prodotto studiato in maniera vincente da Montarbo®, per soddisfare le esigenze nelle situazioni più difficili, dove le condizioni atmosferiche richiedono alte prestazioni e durezza.

*The only loudspeaker to have an ultra-resistant single shell for those wishing to listen to good music, even during the apocalypse.*

*Compact, versatile, light and easy to install, the series comes with great power and sound impact, winning out on all points for discussion and popular and in demand in exorbitant numbers all over the world, thanks to its famous capacity to withstand even the worst weather conditions. This line of loudspeakers has in fact been designed to withstand and hold out over time, without losing its reliability and sound quality; this product has been successfully designed by Montarbo® to meet the demands of the most difficult situations, specifically with difficult weather conditions, where long-lasting resistance and high-tech performances are necessary.*

I tecnici Montarbo® ne suggeriscono le seguenti applicazioni:  
Montarbo® technicians suggest the following applications:

CLUB	CAFÉ	WEATHER
W440A	W440A	W440A
W440P	W440P	W440P
W17P		W17P
		W17As

SPECIFICATIONS	W17As - 2-way active bi-amplified	W440A - 2-way active bi-amplified
Frequency response	40 Hz ÷ 20 kHz ± 3 dB	45 Hz ÷ 20 kHz ± 3 dB
Max SPL	130 dB	128 dB
Components	Custom-designed LF 15" neodymium magnet woofer (3" voice coil) HF 1.4" driver (2.5" voice coil, titanium diaphragm) constant directivity horn (60°H x 40°V)	Custom-designed LF 12" neodymium magnet woofer (2.5" voice coil) HF 1" driver (2" voice coil) constant directivity horn (90°H x 70°V)
Built-in power amplifier Total Output Power	2 class-AB, MosFet, dedicated power units 600 W (LF 450 W + HF 150 W)	2 class-AB, MosFet, dedicated power units 400 W (LF 300 W + HF 100 W)
Dimensions (WxHxD)	480 x 740 x 405 mm	400 x 650 x 355 mm
Weight	32 kg	18.5 kg
Passive versions Dimensions (WxHxD) Weight	W17P: 600 W / 8 Ω 480 x 740 x 405 mm 25 kg	W440P: 400 W / 8 Ω 400 x 650 x 355 mm 14.5 kg